

24 River Road Bogota, NJ 07603-0500 Phone: 1.800.631.8375 Fax: 1.800.888.3315

Fax: 1.800.888.3315 www.outwater.com

RSRS SERIES - SCRATCH RESISTANT SERIES /HIPS

TECHNICAL DATA SHEET: ROLL-A-LAM (#RL-0113-BS)

Physical Properties	<u>Specifications</u>
Substrate:	Styrene (HIPS)
Substrate Colors:	Black, White, Natural and Colors
Substrate Gauges:	.007 to .250 mils
Sheet Size:	Up to 50" width x 144" length
Fabrication Properties:	Router, saw, die-cut, shear
UV Light Resistance:	n/a
Abrasion:	No visible change when tested with 0000 steel wool; <10mg weight loss, CS10F wheels, 250 cycles, 500g/wheel
Chemical Resistance:	Exhibits excellent resistance to alcohols, ketones, hydrocarbons, esters, mild acids, salt solutions, and most household cleaners.
Scratch/Hardness:	H to 2H pencil hardness
Vicat Softening Point	ASTM D-1525 212 degrees F
Specific Gravity	ASTM D-792 1.04 g/cc
Tensile Modulus	ASTM D-638 270,000 psi
Izod Impact	ASTM D-256 @ 73 F 3.5 ft-lbs/in
Flexural Modulus	ASTM D-790 285,000 PSI
Coefficient of Thermal Expansion	ASTM D-696 4.5 x 10-5 in/in/F
Tensile Strength @ Yield	ASTM D-638 3,700 psi
Flexural Strength @ Yield	ASTM D-790 7,000 psi
Heat Deflection Temperature	ASTM D-648 (264 psi unannealed) 185 degrees F
Hardness	ASTM D-785 68 Rockwell R (L)
Flammability	UL Subject 94 HB .062 thickness

All products are sold upon condition that purchasers shall make their own tests to determine the suitability of such products for their particular purposes and uses, and that purchasers assume all risks and liability for the results of use of the products, including use in accordance with seller's recommendations. Nothing in this bulletin constitutes permission or a recommendation to practice or use any invention covered by any patent owned by this company or by others. THERE IS NO WARRANTY OF MERCHANTABILITY OR OF FITNESS FOR ANY PURPOSE. PRODUCTS WILL MEETS SELLER'S STANDARD SPECIFICATIONS THEREFORE, BUT THERE ARE NO OTHER WARRANTIES FOR THE PRODUCTS DESCRIBED.