



24 River Road
Bogota, NJ 07603-0500
Phone: 1.800.631.8375
Fax: 1.800.888.3315
www.outwater.com

ROLL-A-LAM PEEL AND STICK LAMINATE APPLICATION GUIDE HELPFUL HINTS AND INFORMATION SHEET

1. Testing is recommended for all applications. (Especially for larger applications)
2. The smoother the surface the better it will stick. Some surfaces may require sanding.
EXAMPLES:
 - Mirrored doors are bonded to metal frames with peel and stick.
 - Decorative automobile trim is bonded with peel and stick
3. Some substrates/applications may need to be sealed or primed prior to installation.
 - When using any kind of raw wood it is recommended to use the following gloss clear coats:
 - i. Fast drying polyurethane clear gloss superior durability (Suggested brand: Minwax®)
 - ii. Clear wood finish gloss brushing lacquer (Suggested brand: DEFT)
 - Brush on one liberal coat and let it dry for at least 2 hours minimum or the recommended amount of time per the instructions on the can.
4. To obtain optimum adhesion, the bonding surfaces must be clean, dry and well unified; some typical surface cleaning solvents are isopropyl alcohol or heptane.
5. Sawdust is the biggest enemy. Always wipe the surface with a tack cloth or with a sponge such as you would do your kitchen table.
6. Apply the foil as you would do a sheet of wallpaper. If the foil is getting out of line or wrinkles a bit it may be lifted and/or removed and be put back down again and again.
7. Apply pressure with a "Sable" roller, J-roller, or a block of hardwood with a rounded edge.
8. There is enough tack to trim it immediately.
9. Trim the foil with a small hand trimmer. There is one designed for straight edges as well as one for curved surfaces. A square and utility knife is useful for butt joints. Cut from the decorative foil side.
10. Routers and other high speed woodworking tools are not recommended.
11. The glue takes 72 hours to be at 75% of its strength. The glue continues to get stronger.
12. The adhesive of this material is serviceable for short periods (minutes, hours depending on substrate and environment).

IMPORTANT NOTICE TO PURCHASER:

All statements, technical information and recommendations herein are based on tests we believe to be reliable, but the accuracy or completeness thereof is not guaranteed, and the following is made in lieu of all warranties, expressed or implied, including the implied warranties of merchantability and fitness for purpose: The seller's and manufacturer's only obligation shall be to replace such quantity of the product proved to be defective. Before using, user shall determine the suitability of the product for its intended use, and the user assumes all risk and liability whatsoever in connection therewith. NEITHER SELLER NOR MANUFACTURER SHALL BE LIABLE EITHER IN TORT OR IN CONTRACT FOR ANY LOSS OF DAMAGE, DIRECT, INCIDENTAL, OR CONSEQUENTIAL, ARISING OUT OF THE USE OF OR THE INABILITY TO USE THE PRODUCT. No statement or recommendation not contained herein shall have any force or effect unless in an agreement signed by officers of the seller and manufacturer therewith.

Outwater Industries, Inc. assumes no liability for improper installation.