



## RANGE HOOD BLOWER / FAN INSTALLATION

### STEP 1:

Remove adapter/dampers if applicable from the blower/fan.



### STEP 2:

Remove the filter.



### STEP 3:

Remove the electrical compartment cover. Set the cover and screw aside.



### STEP 4:

Remove the hardware bag.



### STEP 5:

Remove the cabinet brackets and set them aside. The unit will not fit through the liner hole if it is not removed.



### STEP 6:

Find the four #8-32 x 1/4" machine screws in the hardware pack.



### STEP 7:

Fit the blower/fan through the hole in the liner. Make sure the lights and controls are at the front of the liner. The back of the liner is shown here.



### STEP 8:

Attach the blower/fan to the liner using the 2 outside holes in the mounting flange on the back of the liner. Carefully thread 2, #8-32 x 1/4" screws into the threaded holes in the blower/fan. Make sure the screws are tight.



### STEP 9:

On the front of the liner attach the blower/fan using the inside 2 holes on the front mounting flange of the liner. Use the 2 remaining #8-32 x 1/4" machine screws. Make sure all the screws are tight. Proceed with the range hood mounting instructions.



24 River Road  
Bogota, NJ 07603  
1.800.631.8375  
[www.outwater.com](http://www.outwater.com)